


TIMING BELT CLAMPING PLATES

Ideal for applications where the belt must be firmly held in one spot. Perfect for use with long length belting.
Supreme Engineers keep a large range of Clamp Plates on the shelf.



CLASSICAL	PART NO	A	A1	A2	B	C	D	E
XL	XL025	42.5	25.4	8.6	25.4	6.0	8.0	5.5
	XL037	42.5	25.4	8.6	28.5	6.0	8.0	5.5
L	L050	76.6	47.6	14.5	39.1	8.0	15.0	9.0
	L075	76.6	47.6	14.5	45.0	8.0	15.0	9.0
	L100	76.6	47.6	14.5	51.5	8.0	15.0	9.0
H	H050	106.9	63.5	21.7	45.0	10.0	22.0	11.0
	H075	106.9	63.5	21.7	51.0	10.0	22.0	11.0
	H100	106.9	63.5	21.7	57.4	10.0	22.0	11.0

TD	PART NO	A	A1	A2	B	C	D	E
5M	5M09	41.8	25.0	8.4	28.0	6.0	8.0	5.5
	5M15	41.8	25.0	8.4	34.0	6.0	8.0	5.5
	5M25	41.8	25.0	8.4	44.0	6.0	8.0	5.5
8M	8M20	66.0	40.0	13.0	45.0	8.0	15.0	9.0
	8M30	66.0	40.0	13.0	55.0	8.0	15.0	9.0
	8M50	66.0	40.0	13.0	75.0	8.0	15.0	9.0
	8M85	66.0	40.0	13.0	110.0	8.0	15.0	9.0
14M	14M40	116.0	70.0	23.0	71.0	10.0	22.0	11.0
	14M55	116.0	70.0	23.0	86.0	10.0	22.0	11.0
	14M85	116.0	70.0	23.0	116.0	10.0	22.0	11.0
	14M115	116.0	70.0	23.0	146.0	10.0	22.0	11.0
	14M170	116.0	70.0	23.0	201.0	10.0	22.0	11.0

METRIC	PART NO	A	A1	A2	B	C	D	E
T5	T5/10	41.8	25.0	8.4	29.0	6.0	8.0	5.5
	T5/16	41.8	25.0	8.4	35.0	6.0	8.0	5.5
	T5/25	41.8	25.0	8.4	44.0	6.0	8.0	5.5
T10	T10/16	80.0	50.0	15.0	41.0	8.0	15.0	9.0
	T10/25	80.0	50.0	15.0	50.0	8.0	15.0	9.0
	T10/32	80.0	50.0	15.0	57.0	8.0	15.0	9.0
	T10/50	80.0	50.0	15.0	75.0	8.0	15.0	9.0
AT5	AT5/10	41.8	25.0	8.4	29.0	6.0	8.0	5.5
	AT5/16	41.8	25.0	8.4	35.0	6.0	8.0	5.5
	AT5/25	41.8	25.0	8.4	44.0	6.0	8.0	5.5
AT10	AT10/16	80.0	50.0	15.0	41.0	8.0	15.0	9.0
	AT10/25	80.0	50.0	15.0	50.0	8.0	15.0	9.0
	AT10/32	80.0	50.0	15.0	57.0	8.0	15.0	9.0
	AT10/50	80.0	50.0	15.0	75.0	8.0	15.0	9.0